

ADVANCED SUBSIDIARY GCE MATHEMATICS (MEI)

Mechanics 1

4761

Candidates answer on the Answer Booklet

OCR Supplied Materials:

- 8 page Answer Booklet
- Graph paper
- MEI Examination Formulae and Tables (MF2)

Other Materials Required:

None

Wednesday 27 January 2010 Afternoon

Duration: 1 hour 30 minutes



INSTRUCTIONS TO CANDIDATES

- Write your name clearly in capital letters, your Centre Number and Candidate Number in the spaces provided on the Answer Booklet.
- Use black ink. Pencil may be used for graphs and diagrams only.
- Read each question carefully and make sure that you know what you have to do before starting your answer.
- Answer all the questions.
- Do **not** write in the bar codes.
- You are permitted to use a graphical calculator in this paper.
- Final answers should be given to a degree of accuracy appropriate to the context.
- The acceleration due to gravity is denoted by $g \, \text{m s}^{-2}$. Unless otherwise instructed, when a numerical value is needed, use g = 9.8.

INFORMATION FOR CANDIDATES

- The number of marks is given in brackets [] at the end of each question or part question.
- You are advised that an answer may receive no marks unless you show sufficient detail of the working to
 indicate that a correct method is being used.
- The total number of marks for this paper is 72.
- This document consists of **8** pages. Any blank pages are indicated.

Section A (36 marks)

1 A ring is moving up and down a vertical pole. The displacement, s m, of the ring above a mark on the pole is modelled by the displacement-time graph shown in Fig. 1. The three sections of the graph are straight lines.




Fig. 1

- (i) Calculate the velocity of the ring in the interval 0 < t < 2 and in the interval 2 < t < 3.5. [2]
- (ii) Sketch a velocity-time graph for the motion of the ring during the 4 seconds. [2]
- (iii) State the direction of motion of the ring when
 - (A) t = 1,
 - (*B*) t = 2.75,

(C)
$$t = 3.25$$
.

- A particle of mass 5 kg has constant acceleration. Initially, the particle is at $\binom{-1}{2}$ m with velocity 2 $\binom{2}{-3}$ m s⁻¹; after 4 seconds the particle has velocity $\binom{12}{9}$ m s⁻¹.
 - (i) Calculate the acceleration of the particle. [2]
 - (ii) Calculate the position of the particle at the end of the 4 seconds. [3]
 - (iii) Calculate the force acting on the particle. [2]

3 In this question, **i** is a horizontal unit vector and **j** is a unit vector pointing vertically upwards.

A force \mathbf{F} is $-\mathbf{i} + 5\mathbf{j}$.

(i) Calculate the magnitude of **F**.

Calculate also the angle between **F** and the upward vertical.

[4]

Force **G** is $2a\mathbf{i} + a\mathbf{j}$ and force **H** is $-2\mathbf{i} + 3b\mathbf{j}$, where a and b are constants. The force **H** is the resultant of forces $4\mathbf{F}$ and \mathbf{G} .

A box of mass 2.5 kg is on a smooth horizontal table, as shown in Fig. 4. A light string AB is attached to the table at A and the box at B. AB is at an angle of 50° to the vertical. Another light string is attached to the box at C; this string is inclined at 15° above the horizontal and the tension in it is 20 N. The box is in equilibrium.




Fig. 4

- (i) Calculate the horizontal component of the force exerted on the box by the string at C. [1]
- (ii) Calculate the tension in the string AB.

[2]

(iii) Calculate the normal reaction of the table on the box.

[4]

The string at C is replaced by one inclined at 15° below the horizontal with the same tension of 20 N.

(iv) Explain why this has no effect on the tension in string AB.

[1]

5 The velocity, $v \,\mathrm{m}\,\mathrm{s}^{-1}$, of a particle moving along a straight line is given by

$$v = 3t^2 - 12t + 14$$
.

where *t* is the time in seconds.

(i) Find an expression for the acceleration of the particle at time t.

[2]

- (ii) Find the displacement of the particle from its position when t = 1 to its position when t = 3. [4]
- (iii) You are *given* that v is always positive. Explain how this tells you that the distance travelled by the particle between t = 1 and t = 3 has the same value as the displacement between these times.

[2]

Section B (36 marks)

6




Fig. 6.1

Fig. 6.1 shows a toy barge A of mass 1.5 kg on a rough plane. The plane is at an angle α to the horizontal where $\sin \alpha = \frac{2}{7}$.

(i) Show that the component of the weight of the barge down the slope is 4.2 N. [2]

The barge is held in equilibrium by a force of 6.4 N acting up and parallel to the plane.

(ii) Determine the frictional force on the barge and state whether it acts up or down the plane. [2]

The force of $6.4 \,\mathrm{N}$ is removed and the barge now slides down the plane with acceleration $1.2 \,\mathrm{m \, s^{-2}}$.

- (iii) Calculate the new frictional force on the barge. [4]
- (iv) Determine how far the barge travels while its speed increases from $0.8 \,\mathrm{m \, s^{-1}}$ to $2 \,\mathrm{m \, s^{-1}}$.

Fig. 6.2 shows barge A on the same slope with a second barge B of mass 2 kg attached to it by means of a light rigid coupling parallel to the plane. The frictional force on barge B is 0.7 N and the frictional force on barge A is now 2.3 N. At one stage of the motion the two barges are being pulled up the plane by a force of 10 N parallel to the plane.




Fig. 6.2

(v) Draw diagrams showing the forces acting on each barge.

Calculate the acceleration of the barges and clearly indicate its direction.

Find the force in the coupling, stating whether this is a tension or a thrust (compression). [7]

7




Fig. 7 shows the graph of $y = \frac{1}{100}(100 + 15x - x^2)$.

For $0 \le x \le 20$, this graph shows the trajectory of a small stone projected from the point Q where y m is the height of the stone above horizontal ground and x m is the horizontal displacement of the stone from O. The stone hits the ground at the point R.

- (i) Write down the height of Q above the ground. [1]
- (ii) Find the horizontal distance from O of the highest point of the trajectory and show that this point is 1.5625 m above the ground. [5]
- (iii) Show that the time taken for the stone to fall from its highest point to the ground is 0.565 seconds, correct to 3 significant figures. [3]
- (iv) Show that the horizontal component of the velocity of the stone is 22.1 m s⁻¹, correct to 3 significant figures. Deduce the time of flight from Q to R. [5]
- (v) Calculate the speed at which the stone hits the ground. [4]

BLANK PAGE

BLANK PAGE



Copyright Information

OCR is committed to seeking permission to reproduce all third-party content that it uses in its assessment materials. OCR has attempted to identify and contact all copyright holders whose work is used in this paper. To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced in the OCR Copyright Acknowledgements Booklet. This is produced for each series of examinations, is given to all schools that receive assessment material and is freely available to download from our public website (www.ocr.org.uk) after the live examination series.

If OCR has unwittingly failed to correctly acknowledge or clear any third-party content in this assessment material, OCR will be happy to correct its mistake at the earliest possible opportunity. For queries or further information please contact the Copyright Team, First Floor, 9 Hills Road, Cambridge CB2 1GE.

OCR is part of the Cambridge Assessment Group; Cambridge Assessment is the brand name of University of Cambridge Local Examinations Syndicate (UCLES), which is itself a department of the University of Cambridge.

4761 Mechanics 1

1 (i)	0 < t < 2, v = 2 $2 < t < 3.5, v = -5$	B1 B1	Condone '5 downwards' and ' – 5 downwards'	
(ii)	$\begin{array}{c} S \\ 2 \\ \hline $		Condone intent – e.g. straight lines free-hand and scales not labelled; accept non-vertical sections at $t = 2 \& 3.5$.	2
	\ 	B1	Only horizontal lines used and 1 st two parts present. BOD <i>t</i> -axis section. One of 1 st 2 sections correct. FT (i) and allow if answer correct with (i) wrong All correct. Accept correct answer with (i) wrong. FT (i) only if 2 nd section –ve in (i)	2
(iii)	(A) upwards; (B) and (C) downwards	E1	All correct. Accept +/- ve but not towards/away from O Accept forwards/backwards. Condone additional wrong statements about position.	1
2 (i)		M1 A1	Use of $\mathbf{v} = \mathbf{u} + \mathbf{a}t$ If vector \mathbf{a} seen, isw.	5
(ii)	either $\mathbf{r} = \begin{pmatrix} -1 \\ 2 \end{pmatrix} + \begin{pmatrix} 2 \\ -3 \end{pmatrix} \times 4 + \frac{1}{2}\mathbf{a} \times 4^{2}$ $\mathbf{r} = \begin{pmatrix} 27 \\ 14 \end{pmatrix} \text{ so } \begin{pmatrix} 27 \\ 14 \end{pmatrix} \text{ m}$ or	M1 A1 A1	For use of $\mathbf{s} = \mathbf{u}t + \frac{1}{2}\mathbf{a}t^2$ with their a. Initial position may be omitted. FT their a. Initial position may be omitted. cao. Do not condone magnitude as final answer. Use of $\mathbf{s} = 0.5t(\mathbf{u} + \mathbf{v})$ Initial position may be omitted.	
		A1 A1	Correct substitution. Initial position may be omitted. cao Do not condone mag as final answer. SC2 for $\binom{28}{12}$	3

(iii)	Using N2L			
	$\mathbf{F} = 5\mathbf{a} = \begin{pmatrix} 12.5 \\ 15 \end{pmatrix} \text{ so } \begin{pmatrix} 12.5 \\ 15 \end{pmatrix} \text{ N}$	M1	Use of $\mathbf{F} = m\mathbf{a}$ or $\mathbf{F} = mg\mathbf{a}$.	
		F1	FT their a only. Do not accept magnitude as final ans.	
				7
				,
3 (i)		M1	Accept $\sqrt{-1^2 + 5^2}$ even if taken to be $\sqrt{24}$	
	$=\sqrt{26} = 5.0990 = 5.10 (3 \text{ s. f.})$	A1		
	Angle with \mathbf{j} is $\arctan(0.2)$	M1	accept $arctan(p)$ where $p = \pm 0.2$ or ± 5 o.e.	
	so 11.309 so 11.3° (3 s. f.)	A1	cao	4
(;;)	(2) (1) (2a)			
(ii)	$ \begin{pmatrix} -2 \\ 3b \end{pmatrix} = 4 \begin{pmatrix} -1 \\ 5 \end{pmatrix} + \begin{pmatrix} 2a \\ a \end{pmatrix} $	M1	$\mathbf{H} = 4\mathbf{F} + \mathbf{G}$ soi	
		M1	Formulating at least 1 scalar equation from their	
	a = 1, b = 7	A1	vector equation soi a correct or G follows from their wrong a	
	so $\mathbf{G} = \begin{pmatrix} 2 \\ 1 \end{pmatrix}$ and $\mathbf{H} = \begin{pmatrix} -2 \\ 21 \end{pmatrix}$	A1	Н сао	
	or $\mathbf{G} = 2\mathbf{i} + \mathbf{j}$ and $\mathbf{H} = -2\mathbf{i} + 21\mathbf{j}$			
	,			4
				8
4(i)	20cos 15 = 19.3185 so 19.3 N (3 s. f.) in direction BC	B1	Accept no direction. Must be evaluated	1
(ii)	Let the tension be T $T \sin 50 = 19.3185$	M1	Accept $\sin \leftrightarrow \cos$ but not (i) $\times \sin 50$	
	so $T = 25.2185$ so 25.2 N (3 s. f.)	F1	FT their 19.3 only. cwo	2
				2
(iii)	$R + 20 \sin 15 - 2.5g - 25.2185 \times \cos 50 = 0$	M1	Allow 1 force missing or 1 tension not resolved. FT <i>T</i> .	
			No extra forces. Accept mass used.	
		B1	Accept sin ↔ cos. Weight correct	
	R = 35.5337 so 35.5 N (3 s. f.)	A1 A1	All correct except sign errors. FT their <i>T</i> cao. Accept 35 or 36 for 2. s.f.	
		A1	Cao. Accept 55 of 50 for 2. s.i.	4
(iv)	The horizontal resolved part of the 20 N	E1	Accept no reference to vertical component but do	
	force is not changed.		not accept 'no change' to both components. No need to be explicit that value of tension in AB	
			depends only on horizontal component of force at C	
				8
	•		•	

		1		
5(i)	a=6t-12	M1	Differentiating	
3(1)	<i>u</i> = 0 <i>t</i> 12	A1	cao	
				2
(ii)	We need $\int_{1}^{3} (3t^2 - 12t + 14) dt$	M1	Integrating. Neglect limits.	
	$= \left[t^3 - 6t^2 + 14t\right]^3$	A1	At least two terms correct. Neglect limits.	
	either			
	= (27 - 54 + 42) - (1 - 6 + 14)	M1	Dep on 1 st M1. Use of limits with attempt at subtraction seen.	
	= 15 - 9 = 6 so 6 m	A1	cao	
	or			
	$s = t^3 - 6t^2 + 14t + C$			
	s = 0 when $t = 1$ gives	M1	Dep on 1 st M1. An attempt to find C using $s(1) = 0$	
	0 = 1 - 6 + 14 + C so $C = -9$		and then evaluating $s(3)$.	
	Put $t = 3$ to give s = 27 - 54 + 42 - 9 = 6 so 6 m.	A1	cao	
	3 27 34 42 7 0 30 0 III.	711	cao	4
(iii)	v > 0 so the particle always travels in the			
(111)	same (+ve) direction	E1	Only award if explicit	
	As the particle never changes direction,	E1	Complete argument	
	the final distance from the starting point			
	is the displacement.			
				8
6 (i)	Component of weight down the plane is			
	$1.5 \times 9.8 \times \frac{2}{7} = 4.2 \text{ N}$	M1	Use of mgk where k involves an attempt at	
		E1	resolution	
		EI	Accept $1.5 \times 9.8 \times \frac{2}{7} = 4.2$ or $14.7 \times \frac{2}{7} = 4.2$ seen	2
				- <u>-</u>
(ii)	Down the plane. Take F down the			
	plane. $4.2 - 6.4 + F = 0$	M1	Allow sign errors. All forces present. No extra	
	1.2 0.1 1	1711	forces.	
	so $F = 2.2$. Friction is 2.2 N down the	A1	Must have direction. [Award 1 for 2.2 N seen and	
	plane		2 for 2.2 N down plane seen]	2
(iii)	F up the plane			
` '	N2L down the plane	M1	N2L. $F = ma$. No extra forces. Allow weight term	
	$4.2 - F = 1.5 \times 1.2$		missing or wrong	
	5 F - 42 19 - 24	A1	Allow only sign errors	
	so $F = 4.2 - 1.8 = 2.4$ Friction is 2.4 N up the plane	A1 A1	± 2.4 cao. Accept no reference to direction if $F = 2.4$.	
	1 Henon 15 2.7 IV up the plane	AI	cao. Accept no reference to uncertoil if $r=2.4$.	4
(iv)	$2^2 = 0.8^2 + 2 \times 1.2 \times s$	M1	Use of $v^2 = u^2 + 2as$ or sequence	
		A1	All correct in 1 or 2-step method	
	s = 1.4 so 1.4 m	A1		2
		J	J	3

either Up the planeM1N2L. $F = ma$. No extra forces. Condone sign errors. All with arrows. All forces present and properly labelled with arrows. $10-3.5\times9.8\times^2_7-(2.3+0.7)=3.5a$ M1N2L. $F = ma$. No extra forces. Condone sign errors. Allow total/part weight or total/part friction omitted (but not both). Allow mass instead of weight and mass/weight not or wrongly resolved. $a=-0.8$ so 0.8 m s $^{-2}$. down the plane $T-2\times9.8\times^2_7-0.7=2\times(-0.8)$ M1N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight component attempted. No extra forces. Condone sign errors. $T=4.7$ so 4.7 N. Tension or (separate equations of motion)A1N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight component attempted. No extra forces. Condone sign errors.Barge AM1N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight component attempted. No extra forces. Condone sign errors.Barge BM1N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight component attempted and weight on friction missing and also allow mass used instead of weight and we not or wrongly resolved. In other equal weight component attempted and friction term present.M1N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight component attempted and friction term present.M1N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight on friction missing and also allow mass used instead of weight and not or wrongly resolved.M1N2L on one barge with their $\pm a$ (\pm 0 or 0 o	(v)	Diagrams	B1	Frictions and coupling force correctly labelled	
either Up the planeM1N2L. $F = ma$. No extra forces. Condone sign errors. Allow total/part weight or total/part friction omitted (but not both). Allow mass instead of weight and mass/weight not or wrongly resolved. $a = -0.8 \text{ so } 0.8 \text{ m s}^2$. down the plane $For barge B$ up the plane $T = 2 \times 9.8 \times \frac{2}{7} - 0.7 = 2 \times (-0.8)$ A1Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ or (separate equations of motion)M1N2L on one barge with their $\pm a$ ($\pm 1.2 \text{ or } 0$). All forces present and weight component attempted. No extra forces. Condone sign errors.Barge AM1N2L on one barge with their $\pm a$ ($\pm 1.2 \text{ or } 0$). All forces present and weight or friction missing and also allow mass used instead of weight and wt not or wrongly resolved. In other equa weight component attempted and friction term present. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors.Barge BM1N2L. Do not allow $F = mga$. No extra forces. Condone sign errors.M1N2L. Do not allow $F = mga$. No extra forces. Condone sign errors.M1N2L. Do not allow $F = mga$. No extra forces. Condone sign errors.M1Solving a pair of equns in a and T (ii) $\frac{1}{2}(20+5)-5=7.5$ M1Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A112.5 o.e. seen A112.5 o.e. seen A112.5 o.e. seen A1A1(ii) $\frac{1}{2}(20+5) = \frac{1}{100}(100+15\times7.5-7.5^2)$ A112.5 o.e. seen as final answer FT their 7.5					
either Up the plane 10-3.5×9.8× $\frac{2}{7}$ -(2.3+0.7)=3.5a M1 N2L. $F = ma$. No extra forces. Condone sign errors. Allow total/part weight or total/part friction omitted (but not both). Allow mass instead of weight and mass/weight not or wrongly resolved. B1 Correct overall mass and friction A1 Clear description or diagram For barge B up the plane $T - 2 \times 9.8 \times \frac{2}{7} - 0.7 = 2 \times (-0.8)$ M1 N2L on one barge with their $\pm a \neq 1.2$ or 0). All forces present and weight component attempted. No extra forces. Condone sign errors. T = 4.7 so 4.7 N. Tension or (separate equations of motion) A1 Barge A Barge A Barge B M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. A1 Clear description or diagram and also allow mass used instead of weight and we not or wrongly resolved. In other equn weight component attempted and friction term present. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. A1 Clear description or diagram and T Clear description or diagram cao ewo T(i) $y(0) = 1$ B1 Either $\frac{1}{2}(20+5) - 5 = 7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 A1 Clear description or diagram cao ewo T(i) $\frac{1}{2}(20+5) - 5 = 7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 A1 A1 A1 A1 A1 A1 Clear description or diagram cao ewo			B1	All forces present and properly labelled with	
Up the plane $10-3.5 \times 9.8 \times \frac{3}{7} - (2.3 + 0.7) = 3.5a$ $10-3.5 \times 9.8 \times \frac{3}{7} - (2.3 + 0.7) = 3.5a$ $10-3.5 \times 9.8 \times \frac{3}{7} - (2.3 + 0.7) = 3.5a$ $10-3.5 \times 9.8 \times \frac{3}{7} - (2.3 + 0.7) = 3.5a$ B1 $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. down the plane For barge B up the plane For barge B up the plane $T - 2 \times 9.8 \times \frac{3}{7} - 0.7 = 2 \times (-0.8)$ T= 4.7 so 4.7 N. Tension or (separate equations of motion) B1 $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. down the plane T= 4.7 so 4.7 N. Tension or (separate equations of motion) A1 Barge A Barge B M1 M2L. On one barge with their $\pm a \neq 1.2 \text{ or } 0$). All forces present and weight component attempted. No extra forces. Condone sign errors. M1 M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 A1 Clear description or diagram condone sign errors. M1 Clear description or diagram errors. M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 A1 Clear description or diagram errors. M1 M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 Clear description or diagram Condone sign errors. M1 Violution 1 and T Clear description or diagram a = -0.8 so 0.8 m s ⁻² . down the plane T= 4.7 so 4.7 N. Tension Tile 1 and 1 and T Clear description or diagram cao ewo Tile 2 and 3 an				1 1 2	
errors. Allow total/part weight or total/part friction omitted (but not both). Allow mass instead of weight and mass/weight not or wrongly resolved. B1 Correct overall mass and friction A1 Clear description or diagram For barge B up the plane $T-2\times9.8\times^2-0.7=2\times(-0.8)$ M1 N2L on one barge with their $\pm a$ ($\neq 1.2$ or 0). All forces present and weight component attempted. No extra forces. Condone sign errors. A1 cao In eom for A or B allow weight or friction missing and also allow mass used instead of weight and wt not or wrongly resolved. In other equn weight component attempted and friction term present. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 Solving a pair of equns in a and a Clear description or diagram cao cwo 7 (i) $y(0) = 1$ B1 Either $\frac{1}{2}(20+5)-5=7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 $\frac{12.5}{2.5}$ o.e. seen A1 $\frac{7}{2.5}$ cao. M1 Attempt at y' and to solve $y' = 0$ A1 $\frac{12.5}{2.5}$ o.e. seen as final answer FT their $\frac{7}{2.5}$ their $\frac{7}{2.5}$ os so 1.5625 m E1 AG		either			
$a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}.$ $down the plane$ For barge B up the plane $T - 2 \times 9.8 \times \frac{2}{7} - 0.7 = 2 \times (-0.8)$ $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ or (separate equations of motion) $A1$ $B1$ $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ or (separate equations of motion) $A1$ $A1$ $A2$ $A3$ $A4$ $A4$ $A4$ $A5$ $A5$ $A5$ $A5$ $A6$ $A6$ $A7$ $A8$ $A8$ $A8$ $A8$ $A9$ $A9$ $A9$ $A9$ $A9$ $A9$ $A9$ $A9$		Up the plane	M1		
$a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}.$ $down the plane$ For barge B up the plane $T - 2 \times 9.8 \times \frac{2}{3} - 0.7 = 2 \times (-0.8)$ M1 N2L. on one barge with their $\pm a \ (\neq 1.2 \text{ or } 0)$. All forces present and weight component attempted. No extra forces. Condone sign errors. $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ or (separate equations of motion) Barge A Barge B M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ M1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ M1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or diagram $T = 4.7 \text{ so } 4.7 \text{ N. Tension}$ A1 Clear description or		$10 - 3.5 \times 9.8 \times \frac{2}{7} - (2.3 + 0.7) = 3.5a$		omitted (but not both). Allow mass instead of weight and mass/weight not or wrongly resolved.	
For barge B up the plane $T-2\times 9.8\times \frac{2}{7}-0.7=2\times (-0.8)$ M1 N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight component attempted. No extra forces. Condone sign errors. A1 cao In eom for A or B allow weight or friction missing and also allow mass used instead of weight and wt not or wrongly resolved. In other equn weight component attempted and friction term present. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. Barge B M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. Solving a pair of equns in a and a and a and a and a and a cao expected by a and		$a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$.	B1	Correct overall mass and friction	
For barge B up the plane $T-2\times 9.8\times \frac{2}{7}-0.7=2\times (-0.8)$ M1 N2L on one barge with their $\pm a$ (\pm 1.2 or 0). All forces present and weight component attempted. No extra forces. Condone sign errors. A1 cao In eom for A or B allow weight or friction missing and also allow mass used instead of weight and wt not or wrongly resolved. In other equn weight component attempted and friction term present. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. Barge B M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. Solving a pair of equns in a and a and a and a cao evo T(i) $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. down the plane $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. down the plane $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. down the plane $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. A1 Clear description or diagram cao evo T(i) $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. M1 Use of symmetry e.g. use of $a = 0.8 \text{ so } 0.8 \text{ m s}^{-2}$. A1 12.5 o.e. seen 7.5 cao M1 A1 N2L no none barge with their $a = 0.8 \text{ so } 0.8 \text{ m}$ and with their $a = 0.8 \text{ so } 0.8 \text{ m}$ in the plane $a = 0.8 \text{ so } 0.8 \text{ m}$ in the plane $a = 0.8 \text{ so } 0.8 \text{ m}$ in $a = 0.8 \text{ so } 0.8 so $			A1	Clear description or diagram	
$T-2\times9.8\times^2_7-0.7=2\times(-0.8)$ $T-2\times9.8\times^2_7-0.7=2\times(-0.8)$ $T=4.7 \text{ so } 4.7 \text{ N. Tension}$ or (separate equations of motion) $T=4.7 \text{ so } 4.7 \text{ N. Tension}$ or (separate equations of motion) $T=4.7 \text{ so } 4.7 \text{ N. Tension}$ $T=4.7 \text{ so } 4.7 N. Tensio$		<u> </u>			
or (separate equations of motion) In eom for A or B allow weight or friction missing and also allow mass used instead of weight and wt not or wrongly resolved. In other equn weight component attempted and friction term present. Barge A M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 Solving a pair of equns in a and a Clear description or diagram cao cwo 7 (i) $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. M1 Use of symmetry e.g. use of $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Use of symmetry e.g. use of $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Use of symmetry e.g. use of $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Use of symmetry e.g. use of $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M2 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M3 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M4 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M5 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M6 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M1 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M2 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M3 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M4 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M5 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M6 Attempt at $a = 0.8 \text{ so } 0.8 \text{ m}^{-2}$. M7 So cao, seen as final answer. M8 Attempt at $a $			M1	forces present and weight component attempted.	
and also allow mass used instead of weight and wt not or wrongly resolved. In other equn weight component attempted and friction term present. M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 Solving a pair of equns in a and a Clear description or diagram cao cwo To iv $y(0) = 1$ B1 Either (ii) $y(0) = 1$ B1 Either (iii) $y(0) = 1$ B1 Use of symmetry e.g. use of $\frac{1}{2}(20 + 5)$ A1 $y(0) = 1$ B1 Tightharpoonup in $y(0) = 1$ A1 $y(0) = 1$ A2 $y(0) = 1$ A3 $y(0) = 1$ A4 $y(0) = 1$ A5 $y(0) = 1$ A6 $y(0) = 1$ A6 $y(0) = 1$ A7 $y(0) = 1$ A8 $y(0) = 1$ A9 $y(0) = 1$ A1 $y(0) = 1$ A1 $y(0) = 1$ A2 $y(0) = 1$ A3 $y(0) = 1$ A4 $y(0) = 1$ A5 $y(0) = 1$ A6 $y(0) = 1$ A7 $y(0) = 1$ A8 $y(0) = 1$ A9 $y(0) = 1$ A1 $y(0) = 1$ A1 $y(0) = 1$ A2 $y(0) = 1$ A3 $y(0) = 1$ A4 $y(0) = 1$ A5 $y(0) = 1$ A6 $y(0) = 1$ A7 $y(0) = 1$ A8 $y(0) = 1$ A9 $y(0) = 1$ A1 $y(0) = 1$ A1 $y(0) = 1$ A2 $y(0) = 1$ A3 $y(0) = 1$ A4 $y(0) = 1$ A5 $y(0) = 1$ A6 $y(0) = 1$ A7 $y(0) = 1$ A8 $y(0) = 1$ A9 $y(0) = 1$ A1 $y(0) = 1$ A1 $y(0) = 1$ A2 $y(0) = 1$ A3 $y(0) = 1$ A4 $y(0) = 1$ A5 $y(0) = 1$ A7 $y(0) = 1$ A8 $y(0) = 1$ A9 $y(0) = 1$ A1 $y(0) = 1$ A1 $y(0) = 1$ A2 $y(0) = 1$ A3 $y(0) = 1$ A4 $y(0) = 1$ A5 $y(0) = 1$ A7 $y(0) = 1$ A8 $y(0) = 1$ A9 $y(0) = 1$ A1		T = 4.7 so 4.7 N. Tension	A1	cao	
Barge A Barge B M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. Solving a pair of equns in a and a and a and a and a clear description or diagram cao cwo 7 (i) $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. M1 Clear description or diagram cao cwo 8 Either (ii) $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. M1 Use of symmetry e.g. use of $a = -0.8 \text{ so } 0.8 \text{ m}^{-2}$. A1 12.5 o.e. seen A1 A1 A1 Clear description or diagram cao cwo A1 A2 A1 A2 A3 A3 A4 A4 A4 A4 A4 A5 A5 A6 A7 A7 A7 A7 A7 A8 A8 A8 A8 A8		or (separate equations of motion)		not or wrongly resolved. In other equn weight	
Barge B M1 N2L. Do not allow $F = mga$. No extra forces. Condone sign errors. Solving a pair of equns in a and T $a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$. down the plane $T = 4.7 \text{ so } 4.7 \text{ N}$. Tension A1 Clear description or diagram cao cwo T(i) $y(0) = 1$ B1 Either $\frac{1}{2}(20+5)-5=7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 12.5 o.e. seen A1 7.5 cao M1 Attempt at y ' and to solve y ' = 0 A1 A1 A1 A1 T.5 cao, seen as final answer $y(7.5) = \frac{1}{100}(100+15\times7.5-7.5^2)$ $y(7.5) = \frac{25}{16}(1.5625) \text{ so } 1.5625 \text{ m}$ E1 AG		Barge A	M1	N2L. Do not allow $F = mga$. No extra forces.	
M1 Solving a pair of equns in a and T Clear description or diagram A1 Clear description or diagram Cao cwo 7 (i) $y(0) = 1$ B1 B1 Either $\frac{1}{2}(20+5)-5=7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 12.5 o.e. seen A1 7.5 cao A1 Attempt at y ' and to solve y ' = 0 A1 $k(15-2x)$ where $k=1$ or $\frac{1}{100}$ A1 7.5 cao, seen as final answer $y(7.5) = \frac{1}{100}(100+15\times7.5-7.5^2)$ A1 AG AG AG AG		Barge B	M1	N2L. Do not allow $F = mga$. No extra forces.	
down the plane $T = 4.7$ so 4.7 N. Tension A1 A1 Clear description or diagram cao cwo 7 (i) $y(0) = 1$ B1 Either $\frac{1}{2}(20+5)-5=7.5$ M1 A1 A1 A1 A2.5 o.e. seen A1 A2.9 where $k = 1$ or $\frac{1}{100}$ A1 A1 A2.5 cao, seen as final answer A1 A2.5 cao, seen as final answer A3 A4 A5 A6			M1		
$T = 4.7$ so 4.7 N. Tension A1 cao cwo $T = 4.7$ so 4.7 N. Tension A1 cao cwo $T = 4.7$ so 4.7 N. Tension B1 $T = 4.7$ so 4.7 N. Tension M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 A1 cao cwo A1 cao cwo $T = 4.7$ so 4.7 N. Tension M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 A1 cao cwo A2 cao cwo $T = 4.7$ so 1.7 cao. A2 cao cwo A3 cao cwo $T = 4.7$ so 1.7 cao. A3 cao cwo A4 cao cwo A4 cao cwo A5 cao cwo A5 cao cwo A6 cao cwo A7 cao cwo A1 cao cwo		$a = -0.8 \text{ so } 0.8 \text{ m s}^{-2}$.			
7 (i) $y(0) = 1$ B1 Either $\frac{1}{2}(20+5) - 5 = 7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 12.5 o.e. seen A1 7.5 cao M1 Attempt at y' and to solve $y' = 0$ A1 $k(15-2x)$ where $k = 1$ or $\frac{1}{100}$ A1 7.5 cao, seen as final answer $y(7.5) = \frac{1}{100}(100+15\times7.5-7.5^2)$ A1 y' A1		down the plane	A 1	Clear description or diagram	
(ii) Either $\frac{1}{2}(20+5)-5=7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 12.5 o.e. seen A1 7.5 cao M1 Attempt at y' and to solve y' = 0 A1 $k(15-2x)$ where $k=1$ or $\frac{1}{100}$ A1 7.5 cao, seen as final answer $y(7.5) = \frac{1}{100}(100+15\times7.5-7.5^2)$ $= \frac{25}{16}(1.5625)$ so 1.5625 m E1 AG		T = 4.7 so 4.7 N. Tension	A1	cao cwo	
(ii) Either $\frac{1}{2}(20+5)-5=7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 12.5 o.e. seen A1 7.5 cao M1 Attempt at y' and to solve y' = 0 A1 $k(15-2x)$ where $k=1$ or $\frac{1}{100}$ A1 7.5 cao, seen as final answer $y(7.5) = \frac{1}{100}(100+15\times7.5-7.5^2)$ $= \frac{25}{16}(1.5625)$ so 1.5625 m E1 AG					7
(ii) Either $\frac{1}{2}(20+5)-5=7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 12.5 o.e. seen A1 7.5 cao M1 Attempt at y' and to solve y' = 0 A1 $k(15-2x)$ where $k=1$ or $\frac{1}{100}$ A1 7.5 cao, seen as final answer $y(7.5) = \frac{1}{100}(100+15\times7.5-7.5^2)$ $= \frac{25}{16} (1.5625) \text{ so } 1.5625 \text{ m}$ EI AG					18
(ii) $\frac{1}{2}(20+5)-5=7.5$ M1 Use of symmetry e.g. use of $\frac{1}{2}(20+5)$ A1 12.5 o.e. seen A1 7.5 cao M1 Attempt at y' and to solve $y'=0$ A1 $k(15-2x)$ where $k=1$ or $\frac{1}{100}$ A1 7.5 cao, seen as final answer FT their 7.5 E1 AG	7 (i)	y(0) = 1	B1		1
or $ \begin{array}{ccccccccccccccccccccccccccccccccccc$		Either			
or $ \begin{array}{ccccccccccccccccccccccccccccccccccc$	(ii)	$\frac{1}{2}(20+5)-5=7.5$	M1	Use of symmetry e.g. use of $\frac{1}{2}(20+5)$	
or $ \begin{array}{ccccccccccccccccccccccccccccccccccc$			A1		
or $ M1 Attempt at y' and to solve y' = 0 A1 k(15-2x) where k = 1 or \frac{1}{100} A1 7.5 cao, seen as final answer y(7.5) = \frac{1}{100} (100 + 15 \times 7.5 - 7.5^{2}) = \frac{25}{16} (1.5625) \text{ so } 1.5625 \text{ m} A1 7.5 cao, seen as final answer FT their 7.5 E1 AG $					
$y(7.5) = \frac{1}{100} (100 + 15 \times 7.5 - 7.5^2)$ $= \frac{25}{16} (1.5625) \text{ so } 1.5625 \text{ m}$ A1 A1 T.5 cao, seen as final answer FT their 7.5 E1 AG		or		Attempt at y' and to solve $y' = 0$	
$y(7.5) = \frac{1}{100} (100 + 15 \times 7.5 - 7.5^2)$ $= \frac{25}{16} (1.5625) \text{ so } 1.5625 \text{ m}$ A1 A1 A2 T.5 cao, seen as final answer FT their 7.5 E1 AG			A1	1 7	
$y(7.5) = \frac{1}{100} (100 + 15 \times 7.5 - 7.5^2)$ M1 FT their 7.5 = $\frac{25}{16}$ (1.5625) so 1.5625 m E1 AG			A 1	100	
		$y(7.5) = \frac{1}{100} (100 + 15 \times 7.5 - 7.5^2)$			
		$=\frac{25}{16}$ (1.5625) so 1.5625 m	E1	AG	
[SC2 only showing 1.3623 leads to $x = 7.3$]				[SC2 only showing 1.5625 leads to $x = 7.5$]	5

(iii)	$4.9t^2 = \frac{25}{16} \ (1.5625)$	M1	Use of $s = ut + 0.5at^2$ with $u = 0$. Condone use of ± 10 , ± 9.8 , ± 9.81 . If sequence of <i>suvat</i> used, complete method required. In any method only error accepted is sign error	
	$t^2 = 0.31887$ so $t = \pm 0.56469$ Hence 0.565 s (3 s. f.)	E1	AG. Condone no reference to –ve value. www. 0.565 must be justified as answer to 3 s. f.	3
(iv)	$\dot{x} = \frac{12.5}{0.56469} = 22.1359$	M1	or 25 / (2×0.56469)	
	so 22.1 m s ⁻¹ (3 s. f.))	B1 E1	Use of 12.5 or equivalent 22.1 must be justified as answer to 3 s. f. Don't penalise if penalty already given in (iii).	
	Either Time is $\frac{20}{12.5} \times 0.56469 \text{ s}$	M1		
	so 0.904 s (3 s. f.)	A1	cao Accept 0.91 (2 s. f.)	
	Time is $\frac{20}{22.1359}$ s	M1		
	= 0.903507 so 0.904 s (3 s. f.) or	A1	cao Accept 0.91 (2 s. f.)	
	$(iii) + \frac{7.5}{\text{their } \dot{x}}$	M1		
	so 0.904 s (3 s. f.)	A1	cao Accept 0.91 (2 s. f.)	5
(v)	$v = \sqrt{\dot{x}^2 + \dot{y}^2}$	M1	Must have attempts at both components	
	$\dot{y}^2 = 0^2 + 2 \times 9.8 \times \frac{25}{16}$ or $\dot{y} = 0 + 9.8 \times 0.5646$	M1	Or equiv. $u = 0$. Condone use of $\pm 10, \pm 9.8, \pm 9.81$.	
	$= \frac{245}{8} (30.625) \qquad \text{or} \dot{y} = \pm 5.539$	A1	Accept wrong s (or t in alternative method) Or equivalent. May be implied. Could come from (iii) if $v^2 = u^2 + 2as$ used there. Award marks again.	
	so $v = \sqrt{490 + 30.625} = 22.8172$ m s ⁻¹ so 22.8 m s ⁻¹ (3 s. f.)	A1	cao. www	4
				18

4761 Mechanics 1

General Comments

There were many candidates who submitted good, well-presented scripts which showed their sound grasp of the principles and their ability to apply them accurately. Most of the candidates were able to make progress with all of the questions and many produced good answers to all of them; the mistakes mentioned in the detailed analysis below of the candidates' responses should be viewed in this context.

Two matters that were not done well by a surprisingly large number of the candidates were the interpretation and construction of kinematics diagrams in Q1 and the production of the force diagram in Q6 (v); there are more details about these matters below.

It was very pleasing to read the many excellent explanations given in answer to Q4 (iii) and to Q5 (iii) from candidates who clearly exactly understood the points they were trying to make.

Comments on Individual Questions

Section A (36 marks)

1 Construction and use of kinematics graphs

Many candidates failed to score full marks. The meaning of the language of kinematics is not completely understood by many candidates and quite a few do not understand at all well how to interpret a kinematics graph.

- (i) This was done well by most but by no means all of the candidates. Some candidates did not realise they only had to find gradients; few of those who tried to use the *suvat* results instead made much progress. A common error was to give the speed instead of the velocity for 2 < t < 3.5.
- (ii) Most candidates did this part quite well but some did not use horizontal lines or plotted speeds instead of velocities for 2 < t < 3.5, even when their answer in part (i) was correct.
- (iii) Most candidates understood what was required but a few answered in terms of moving towards or away from O. Perhaps because of misreading the graph, some said that the ring was not moving when t = 3.25.

2 Kinematics and the use of Newton's second law in vector form

Quite a lot of the candidates did this question very well, working accurately throughout in vector forms. Quite a common error was to substitute the initial position where the initial velocity was required throughout the question or just in part (ii).

(i) Most candidates did this accurately but a few gave the magnitude as their final answer.

- (ii) This part was not done so well. Most candidates worked throughout in vector form and gave a vector answer but many failed to take account of the initial position.
- (iii) Most candidates did this part well.

The magnitude and direction of a vector; solving a vector equation.

- (i) This was done well by most of the candidates with the common error being to find the wrong angle.
- (ii) It was pleasing to see so many candidates working efficiently at this problem. Although many candidates knew exactly what to do, others failed to get $\mathbf{H} = 4\mathbf{F} + \mathbf{G}$ or, having found it, didn't know how to extract scalar equations from it. A surprisingly large number found a and b but did not then state \mathbf{G} and \mathbf{H} (or got them wrong).

4 A box in equilibrium with two strings attached

This static equilibrium problem received sensible analysis from many of the candidates. It seemed that fewer candidates than in recent series confused sine and cosine. As always, finding a normal reaction presented too much complexity to candidates who lacked a systematic approach.

- (i) This part was done well by most of the candidates.
- (ii) Although quite a few candidates unnecessarily 'started again', there were many correct answers. The most common error was to resolve the tension in the string at C (or the value found in part (i)) in the direction of AB instead of considering the horizontal components of the two strings.
- (iii) Although there were many correct answers, many more were spoiled by one or more of the following: confusing sine and cosine; omission of a tension; omission of resolution of one or more of the tensions; sign errors.
- (iv) Very many good answers were seen from candidates who had clearly understood that the size of the force in AB depended only on the horizontal component of the force acting at C and that this latter value had not changed. Common errors were simply to claim that it was because the system is still in equilibrium or instead (or as well) to list (some of) the modelling terms 'light' and 'smooth' used in the question.

5 The kinematics of a particle with non-constant acceleration

It was a pleasure to see so many completely correct answers to this question, including the explanation required in part (iii).

(i) Almost all of the candidates answered this part correctly, even those who used constant acceleration results in part (ii).

- (ii) Some candidates tried to use the constant acceleration results but a large majority used the correct method of integration. A surprisingly common error was for the '14' to become '4' in a miscopy at some stage of the working. A quite common mistake was to find the values of the integral for t = 3 and t = 1 but not subtract them.
- (iii) A very pleasing number of candidates clearly understood that the key point is that v > 0 at all times means that the particle does not change direction. A few candidates seemed to have the wrong idea but rather more did not express themselves clearly enough to receive full marks often their difficulty seemed to come from not clearly distinguishing between distance and distance travelled.

Section B (36 marks)

6 Situations on an inclined plane involving friction. After considering static equilibrium this is followed by application of Newton's second law to one body and then two connected bodies.

There were many good answers to all parts of this question except (v). It was expected that the complete analysis of this situation would be challenging to all but the strongest candidates but it was surprising how few candidates could produce diagrams showing the forces acting on each barge. Many candidates did not apply the rule that forces should the have same label if and only if they are known to have the same magnitude. Many candidates missed out one force due to the coupling or did not get the weights or the normal reactions in the correct directions.

- (i) Most candidates did this part correctly but some failed fully to show the given result.
- (ii) Most candidates answered this well but some did not state the direction of the frictional force.
- (iii) Many candidates knew what to do but quite a few of these made a mistake with signs. Common errors were to continue to involve the 6.4 N force or to start again and this time confuse sine and cosine.
- (iv) Most of the candidates obtained full marks for this part. Most calculated the displacement directly but quite a few unnecessarily used a two-step method and found the time first.
- (v) Most of the diagrams given were poor for the reasons given above and few candidates obtained both marks. Whether the equations of motion of each barge or the equation of motion of the pair of barges was attempted, the most common error was to omit either the weight components or, less commonly, the friction terms. A surprisingly large number of those candidates who considered the barges separately omitted the tension terms. Many candidates produced complete and accurate numerical solutions without full (or any) marks for the diagram.

7 Various questions about the motion of a projectile with the trajectory equation as the initial given information

No question about a projectile set in an earlier series has started with the equation of its trajectory and so this question was structured to lead the candidates through a strategy to establish the required results. After parts (i) and (ii) (which were managed by most candidates), the rest of the question, as usual, required increasing levels of understanding of projectile motion. Most candidates worked parts (iii) and (iv) in the order given and many of these made a lot of progress and scored full or nearly full marks; many of the candidates who tried a different order failed to make much progress. A few candidates adopted approaches to the solutions that involved their knowledge of a general trajectory equation and some of these were successful. A mistake seen more than once was differentiating to find $\frac{dy}{dx}$ and then treating it as if it were $\frac{dy}{dt}$.

- (i) Almost all of the candidates scored this mark.
- (ii) The most common method for finding the horizontal position of the highest point was to argue from symmetry but many candidates used calculus. Most candidates who used either argument clearly obtained the correct value. Almost all candidates found the required height by substituting the x value they had just found in the trajectory equation.
- (iii) Many candidates knew how to do this but quite a few made sign errors in their substitution of $s = ut + \frac{1}{2}at^2$. Candidates were expected properly to show that their answer agreed to 0.565 to 3 significant figures and many did not do so.
- (iv) Most candidates who attempted this could see how to obtain the given horizontal component of velocity. As in part (iii), candidates were expected properly to show that their answer agreed to the given one to 3 significant figures and many did not do so – they were not penalised for this omission in both parts (iii) and (iv).
 - Although there are many ways to find the time of flight from Q to R, a few candidates who attempted this part were unable to find any of them. This request also seems to have been overlooked by quite a few candidates.
- (v) A pleasingly large proportion of the candidates knew what to do and did it accurately. By far the most common error was to give the vertical component of the velocity at R instead of the speed.